

RGT-RC Self-adhesive Road Crack Repairing

Description

Self-adhesive Road Repair Tape is a new type of sealing material with flexibility, impact resistance and self-adhesive, generated after a series of physical and chemical reactions of asphalt, modifier and some special organic polymer materials. It is a product of strip shape, with 3cm-5cm width and 3mm-5mm thickness.

When the crack is repaired, it is stuck on the crack along the direction of the crack, and is effectively bonded to the crack on the road surface by manual pressing, and the bonding effect is strengthened by the rolling of the vehicle to prevent the water damage of the road surface.



Advantage

- The seaming tape can be bent, flipped and superimposed at will, and is suitable for crack repair of various shapes and degrees.
- Strong adhesion, the vehicle does not fall off after paving.
- High temperature does not flow, ensuring stability in high temperature areas in summer.
- Low temperature crack resistance, ensuring no cracking in winter.
- Crack sealing effect is good, no water seepage after sealing.

- Easy and fast operation, no professional training required.
- Cracks do not need to be grooved to avoid cracks artificially expanding.
- The product has a long period of validity and can last for more than 3 years.
- Stitching with no burrs and beautiful appearance

Application

It is mainly used for pavement crack treatment, and can also be used for drainage well treatment, tunnel crack waterproof treatment, water body engineering waterproof treatment, etc.

It is suitable for crack repair at various temperatures. When the road temperature is higher than 10 °C, cold paste is used, and when it is lower than 10 celsius, hot paste is used.

Suitable for crack repair in a variety of shapes and degrees.

Contact US

Beijing RongGuan JIAYE Technology Co.LTD

Telephone: +86 (10) 57389866

Email: RGJIAYE@rgjytech.com

Website: www.rgjytech.com

Product Disclaimer

This Product Data Sheet (PDS) summarizes our best knowledge of the product, including how to use and apply the product based on the information available at the time. You should read this TDS carefully and consider the information in the context of how the product will be used, including in conjunction with any other product and the type of surfaces to, and the manner in which, the product will be applied. Our responsibility for products sold is subject to our standard terms and conditions of sale. RG JIAYE does not accept any liability either directly or indirectly for any losses suffered in connection with the use or application of the product whether or not in accordance with any advice, specification, recommendation or information given by it.